



## Type

### Cable

Designation:

Sheath material:

Frequency:

### Plug

Push-on connector type 1:

Push-on connector type 2:

Pin assignment:

### Flame proof

### Oil-resistant

### Norms and standards

### Preferred types

### Characteristics

### Options

## Patch Cable M12 LAN-Industry IP67, Drag Chain

LAN industry 4x2x0,15

PUR

up to 100 MHz

M12-Connector bush shielded

M12-Buchse bush shielded

D-coded according to DKE/IEC 61076-2-101

acc. to IEC 60332-1-2

Acc. to EN60811-2-1

Components of HELUKAT® CONNECTING SYSTEMS® to 100 MHz acc. Categorie 5, ISO 11801 1st Edition. Plug according IEC 61076-2-101-A1. Support the "IAONA Industrial Ethernet Guide" Release 4.0.

Part no.	Sheath colour	Length in metres	Unit
<b>800800</b>	green	0,3	10
<b>800801</b>	green	1,0	10
<b>800802</b>	green	2,0	10
<b>800803</b>	green	3,0	10
<b>800804</b>	green	5,0	10
<b>800805</b>	green	10,0	10

Dimensions and specifications may be changed without prior notice.

- Drag Chain suitable
- Bending radius 7,5 x cable outerdiameter maximum
- Moving speed 180 m/min maximum
- Movement distance 6 m maximum
- Acceleration 5 m/s<sup>2</sup> maximum
- Cycles maximum 10 Mio.
- Temperature range from -40°C to +80°C
- Transmission rate maximum 100 Mbit/s
- Transmission distance maximum 50 m from the Hub to the receiver
- PIN 1 = whog, PIN 3 = og, PIN 2 = whgn, PIN 4 = gn
- Suitable for the „Heavy-Duty“ range

We also can deliver other cable length, other pin codes or other types of plugs.