



## Type

## Patch Cable RJ45 HARTING Industrial IP20, LAN-Industry flexible

### Cable

Designation:

SF/UTP 4x2xAWG 26/7 PUR

Sheath material:

PUR

Frequency:

up to 100 MHz

### Plug

Push-on connector type 1:

RJ45-connector IP20

Push-on connector type 2:

RJ45-connector IP20

System type:

Harting IP20 Industrial 4P

Pin assignment:

1:1 acc. to TIA/EIA 568 B

### Flame proof

acc. to IEC 60332-1-2

### Oil-resistant

Acc. to EN60811-2-1

### Norms and standards

Components of HELUKAT® CONNECTING SYSTEMS® to 100 MHz acc. Categorie 5, ISO 11801 1st Edition, EN 50173-3, EIA/TIA 568 B and IEC 60603-7.

### Preferred types

Part no.	Sheath colour	Length in metres	Unit
<b>800839</b>	grey	0,5	10
<b>800840</b>	grey	1,0	10
<b>800841</b>	grey	2,0	10
<b>800842</b>	grey	3,0	10
<b>800843</b>	grey	5,0	10
<b>800844</b>	grey	10,0	10

Dimensions and specifications may be changed without prior notice.

### Characteristics

- Suitable for using in rough environs
- Suitable for normal movements
- Temperature range from -20°C to +60°C
- Transmission rate maximum 100 Mbit/s
- Transmission distance maximum 30m from the Hub to the receiver
- Suitable for the „Light-Duty“ range

### Options

We also can deliver other cable length, cross-over cables or other types of plugs.