



Type

Cable structure

Housing material:

Colour:

Max. number of modules:

Screen removal:

Strain relief:

Cover lock:

Basic Panel

Steel plate, solid

Grey similar to RAL 7035

8

via continuous screening tape

by means of cable straps

Quick-action twist lock

Dimension

Width:

195 mm

Depth:

150 mm

Number of height modules (HM):

1

Part no.:

801311

Packing unit:

5

Type

Plug type A:

Pin Code A:

Plug type B:

Pin Code B:

Shielding:

Part no.:

801314

Packing unit:

10

Modul for top-hat rail installation patch panel, 2xST MM

-

-

-

-

Modul for top-hat rail installation patch panel, 2xSC MM

-

-

-

-

Type

Plug type A:

Pin Code A:

Plug type B:

Pin Code B:

Shielding:

Part no.:

801315

Packing unit:

1

Norms and standards

HELUKAT® CONNECTING SYSTEMS® INDUSTRY individual system components, category 6 de-embedded (IEC 60603-7-5), ISO 11801 2nd Edition, EN 50173-1 2nd Edition, EIA/TIA 568-B.2-1 and EN 55022 (EMV).

Application

As connection distribution unit for DIN rail installation e.g. in the switch cabinet, for applications involving digital and analog image, data and voice transmission. Can be combined (also with fibre optic components) thanks to the modular structure. Tool-free turn latches enable simple closing and opening of the housing.

Dimensions and specifications may be changed without prior notice.