

Machine outlet IP65

INDUSTRIAL ETHERNET



SC MM, IP65



Type

Industrial Ethernet outlet plastic IP 65, SCdx POF/HCS/MM

Configuration

Housing material:
Colour:
Outlet direction:
Type of fastening:
Dust protection:
Protection classification (IP):

Aluminium die-cast
Grey similar to RAL 7032
Straight
Screw
Hinged cover
65

Equipment

Type:
Number of couplings:
Suitable for fibre type:

Coupler
SC
2
POF/HCS/MM

Dimension

125 x 80 x 57mm

Area of application

Industrial environment

Part no.

801421

Dimensions and specifications may be changed without prior notice.

Packing unit

5

Norms and standards

HELUCOM CONNECTING SYSTEMS® INDUSTRY component suitable for POF, HCS and multimode fibre applications (980/1000µm, 200/230µm, 50/125µm and 62.5/125µm). More they satisfy the MICE specifications, EMC requirements in accordance with DIN EN 61000, and the IP65 housing protection class requirements. The socket can be used in a temperature range of 0°C to +70°C.

Application

Robust data connection socket (shielded) for extreme implementation. Robust plastic housing, and satisfies all mechanical requirements like vibration, shock, and transverse forces. The socket is used either on the machine distributor (MD) or wall mounted directly on the machine (MC) as connection unit.