

Patch Cables PROFINet C



RJ45-HAN® PushPull, IP65/67



Type

Patch Cable RJ45 HARTING Push-Pull IP67, PROFINet C Drag Chain

Cable

Designation:
Sheath material:
Frequency:

PROFINet type C (SK)
PUR
up to 100 MHz

Plug

Push-on connector type 1:
Push-on connector type 2:
System type:
Pin assignment:

RJ45-connector IP67
RJ45-connector IP67
Harting IP65/67 HAN® PushPull 4P plastic
1:1 acc. to TIA/EIA 568 B

Flame proof

acc. to IEC 60332-1-2

Oil-resistant

Acc. to EN60811-2-1

Norms and standards

Components of HELUKAT® CONNECTING SYSTEMS® to 100 MHz acc. Categorie 5, ISO 11801 1st Edition, EN 50173-1, EIA/TIA 568 B and ISO/IEC 24702 - variant 14 (AIDA konform). Support the PROFINet guideline V 1.8.

Preferred types

Part no.	Sheath colour	Length in metres	Unit
802395	green	0,5	10
802396	green	1,0	10
802397	green	2,0	10
802398	green	3,0	10
802399	green	5,0	10
802400	green	10,0	10

Dimensions and specifications may be changed without prior notice.

Characteristics

- Drag Chain suitable
- Bending radius 7,5 x cable outerdiameter maximum
- Moving speed 240 m/min maximum
- Movement distance 10 m maximum
- Acceleration 4 m/s² maximum
- Cycles maximum 5 Mio.
- Temperature range from -40°C to +80°C
- Transmission rate maximum 100 Mbit/s
- Transmission distance maximum 100 m from the Hub to the receiver
- Suitable for the „Heavy-Duty“ range.

Options

We also can deliver other cable length, cross-over cables or other types of plugs.