

Plastic Fibre Cable PROFnet

POF/PA

HELUCOM®

I-V4Y(ZN)Y (type B), I-V4Y(ZN)11Y (type C)



Cable structure

Fibre type: POF 980/1000
Fibre cladding: PA



Optical characteristic

Refractive index core: 1,492
Refractive index cladding: 1,419
Numerical aperture: 0,5
Attenuation see table

Temperature range

Laying, min.: -10°C
Laying, max.: +50°C
Operating, min.: -30°C
Operating, max.: +70°C

Designation	Outer sheath material	Sheath colour	Outer Ø app. mm	Max. tensile force N	Min. stat. bending radius mm	Fibre attenuation	Oil-resistant	Acc. to DESINA®	Weight kg / km	Part no.
I-V4Y(ZN)Y 2P980/1000µm, fixed installation	PVC	Green	7,8	100	100,0	160A1	yes	no	59,0	805686
I-V4Y(ZN)11Y 2P980/1000 green, Drag Chain	PUR	Green	8,0	200	120,0	180A1	yes	no	60,0	805838

Dimensions and specifications may be changed without prior notice.

Application

Signal lines as plastic optical fibre. The use of these transmission systems significantly reduces the number of different cables in a planned bus installation in machine tools operations. Furthermore, possible EMC problems are prevented by the metal-free construction. The main fields of these cables are in machine construction and automobile industry. Installations for example in fixed installed rough areas (type B) or in Drag Chains (type C) are possible. The types on this page are especially constructed for communication within PROFnet systems.