

AGDR-PE connecting thread sealing ring



AGDR-PE

Threaded connection rings for sealing against water and dust.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction


Material

Polyethylene

- halogen-free
- phosphor-free
- cadmium-free

Technical data

Temperature range: -30°C up to +70°C



Dimensions

D Outer diameter
d Inner diameter
h Thickness

for metric thread

Part no.	Size	Inner Ø mm	Outer Ø mm	Thickness mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
90890	M12 x 1,5	12,0	16,0	2,0	500	o. r.	o. r.	o. r.
90891	M16 x 1,5	16,0	20,0	2,0	500	o. r.	o. r.	o. r.
90892	M20 x 1,5	20,0	25,0	2,0	500	o. r.	o. r.	o. r.
90893	M25 x 1,5	25,0	31,0	2,0	500	o. r.	o. r.	o. r.
90894	M32 x 1,5	32,0	38,0	2,0	250	o. r.	o. r.	o. r.
90896	M50 x 1,5	50,0	58,0	2,0	50	o. r.	o. r.	o. r.
90897	M63 x 1,5	63,0	72,0	2,0	50	o. r.	o. r.	o. r.

for PG thread

Part no.	Size	Inner Ø mm	Outer Ø mm	Thickness mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
96529	7	12,5	16,5	1,5	500	o. r.	o. r.	o. r.
96530	9	15,2	19,0	1,5	500	o. r.	o. r.	o. r.
96531	11	18,6	22,5	1,5	500	o. r.	o. r.	o. r.
96532	13,5	20,4	25,0	1,5	500	o. r.	o. r.	o. r.
96533	16	22,5	27,0	1,5	500	o. r.	o. r.	o. r.
96534	21	28,3	33,5	2,0	500	o. r.	o. r.	o. r.
96535	29	37,0	43,5	2,0	250	o. r.	o. r.	o. r.
96537	42	54,0	63,0	2,0	50	o. r.	o. r.	o. r.
96538	48	59,3	69,0	2,0	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request