

# Anaconda Sealtite® HC for extensive temperature ranges



## HC

For extensive temperature ranges.  
Protection tubes from reinforced, galvanised steel band with spiral wound, latched profile, a continuous cord seal and extruded plastic sheath.

This complex construction method keeps the plastic sheath and the internal tube flush together.

## Material

Galvanised steel  
UV-resistant

Outer sheath material: PVC

## Note

Suitable connection glands:  
LT straight, LT angled, T&B straight, T&B angled.

## Technical data

Protection class: IP 67

Temperature range: -45°C up to +105°C  
Temperature range temporary up to +120°C

| Part no.<br>black | Trade size<br>inch | Inner Ø<br>mm | Outer Ø<br>mm | Per<br>metres | Net EUR/100 metres at a purchase of |           |            |
|-------------------|--------------------|---------------|---------------|---------------|-------------------------------------|-----------|------------|
|                   |                    |               |               |               | up to 100                           | 101 - 500 | 501 - 1000 |
| 91238             | 3/8"               | 12,6          | 17,8          | 75            | o. r.                               | o. r.     | o. r.      |
| 91239             | 1/2"               | 16,0          | 21,1          | 60            | o. r.                               | o. r.     | o. r.      |
| 91240             | 3/4"               | 21,0          | 26,4          | 50            | o. r.                               | o. r.     | o. r.      |
| 91241             | 1"                 | 26,5          | 33,1          | 30            | o. r.                               | o. r.     | o. r.      |
| 91242             | 1 1/4"             | 35,1          | 41,8          | 30            | o. r.                               | o. r.     | o. r.      |
| 91243             | 1 1/2"             | 40,3          | 47,8          | 15            | o. r.                               | o. r.     | o. r.      |
| 91244             | 2"                 | 51,6          | 59,9          | 15            | o. r.                               | o. r.     | o. r.      |

Dimensions and specifications may be changed without prior notice.

o. r. = on request