



<p><b>HCX</b> For extensive temperature ranges. Protection tubes from reinforced, galvanised steel band with spiral wound, latched profile, a continuous cord seal and extruded plastic sheath. This complex construction method keeps the plastic sheath and the internal tube flush together.</p>	<p><b>Material</b> Galvanised steel UV-resistant  Outer sheath material: Elastomer</p>	<p><b>Technical data</b> Protection class: IP 67  Temperature range: -55°C up to +145°C Temperature range temporary up to +160°C</p>
	<p><b>Note</b> Suitable connection glands: LT straight, LT angled, T&amp;B straight, T&amp;B angled</p>	

Part no. black	Trade size inch	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
94735	3/8"	12,6	17,8	30	o. r.	o. r.	o. r.
96410	1/2"	16,0	21,1	30	o. r.	o. r.	o. r.
96954	3/4"	21,0	26,4	30	o. r.	o. r.	o. r.
97945	1"	26,5	33,1	30	o. r.	o. r.	o. r.
96247	1 1/4"	35,1	41,8	15	o. r.	o. r.	o. r.
97668	1 1/2"	40,3	47,8	15	o. r.	o. r.	o. r.
97811	2"	51,6	59,9	15	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request