

DC compression cable lug - straight

not insulated



Tubular cable lug DC


Non-insulated tubular cable lugs in eye type design for conductor arrangement RM, to DIN 46235.

Material

Copper
Surface: tinned

Note

Code type indicates the required hexagonal clamping insert.
Part No. 93223 and 93211 are not manufactured to DIN.



Diameter

- a Diameter of the boring
- d Inner diameter of the canle insertion
- b Flange width
- l Length till middle of the boring

eye type

Part no.	Type	Cross-section mm ²	a mm	d mm	b mm	l mm	Code type	Weight kg / 1000 items	Unit	Net EUR/100 items at a purchase of		
										up to 100	101 - 500	501 - 1000
93221	DC 6-6	6,0	6,4	3,8	8,5	24,0	10,0	3,2	50	o. r.	o. r.	o. r.
93222	DC 10-6	10,0	6,4	4,5	9,0	27,0	10,0	3,8	50	o. r.	o. r.	o. r.
93223	DC 10-8	10,0	8,4	4,5	13,0	27,0	10,0	3,8	50	o. r.	o. r.	o. r.
93234	DC 16-6	16,0	6,4	5,5	13,0	36,0	20,0	13,2	50	o. r.	o. r.	o. r.
93210	DC 16-10	16,0	10,5	5,5	17,0	36,0	20,0	13,1	50	o. r.	o. r.	o. r.
93211	DC 25-12	25,0	13,0	7,0	19,0	38,0	20,0	16,5	50	o. r.	o. r.	o. r.
98919	DC 35-10	35,0	10,5	8,2	19,0	42,0	20,0	33,4	50	o. r.	o. r.	o. r.
93212	DC 35-12	35,0	13,0	8,2	21,0	42,0	20,0	32,1	50	o. r.	o. r.	o. r.
93213	DC 50-12	50,0	13,0	10,0	24,0	52,0	28,0	50,6	50	o. r.	o. r.	o. r.
93214	DC 70-12	70,0	13,0	11,5	24,0	55,0	28,0	68,0	25	o. r.	o. r.	o. r.
93215	DC 95-12	95,0	13,0	13,5	28,0	65,0	35,0	93,3	25	o. r.	o. r.	o. r.
93246	DC 95-16	95,0	17,0	13,5	32,0	65,0	35,0	95,8	25	o. r.	o. r.	o. r.
93247	DC 120-10	120,0	10,5	15,5	32,0	70,0	35,0	113,6	25	o. r.	o. r.	o. r.
93216	DC 120-12	120,0	13,0	15,5	32,0	70,0	35,0	112,8	25	o. r.	o. r.	o. r.
93248	DC 120-16	120,0	17,0	15,5	32,0	70,0	35,0	116,3	25	o. r.	o. r.	o. r.
93249	DC 150-10	150,0	10,5	17,0	34,0	78,0	35,0	169,7	10	o. r.	o. r.	o. r.
93217	DC 150-12	150,0	13,0	17,0	34,0	78,0	35,0	151,6	10	o. r.	o. r.	o. r.
93250	DC 150-16	150,0	17,0	17,0	34,0	78,0	35,0	166,8	10	o. r.	o. r.	o. r.
93251	DC 185-10	185,0	10,5	19,0	37,0	82,0	40,0	189,6	5	o. r.	o. r.	o. r.
93218	DC 185-12	185,0	13,0	19,0	37,0	82,0	40,0	188,9	5	o. r.	o. r.	o. r.
93252	DC 185-16	185,0	17,0	19,0	37,0	82,0	40,0	199,2	5	o. r.	o. r.	o. r.
98918	DC 240-12	240,0	13,0	21,5	42,0	92,0	40,0	275,5	1	o. r.	o. r.	o. r.
93253	DC 240-16	240,0	17,0	21,5	42,0	92,0	40,0	284,4	1	o. r.	o. r.	o. r.
93220	DC 300-16	300,0	17,0	24,5	48,0	100,0	50,0	324,6	1	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request