

# DUO core end sleeves

insulated - for 2 conductors



## DUO

Insulated DUO core end sleeves for insertion of 2 conductors prevent stripped wires from fanning.

The hopper-shaped plastic collar enables them to be pushed easily onto the wires. To DIN, ZF, and Telemecanique colour code.

## Material

Sleeve: copper  
Surface: tinned


Insulating shroud: polypropylene

## Note

Versions:  
N = normal  
L = long

## Technical data

Temperature range: up to +105°C  
Temperature range temporary up to +120°C



## Dimensions

L Total length  
l Stick length

Part no.	Size mm <sup>2</sup>	Colour	Colour code	Total length mm	Stick length mm	Unit	Net EUR/100 items at a purchase of			
							up to 5000	5001 - 10000	10001 - 50000	
91622	2x 0.5 / N	white	DIN	15,0	8,0	500	o. r.	o. r.	o. r.	
91623	2x 0.5 / N	orange	Z+F	15,0	8,0	500	o. r.	o. r.	o. r.	
91652	2x 0.75 / L	grey	DIN	17,0	10,0	500	o. r.	o. r.	o. r.	
91671	2x 0.75 / L	light blue	Telemecanique	17,0	10,0	500	o. r.	o. r.	o. r.	
91651	2x 0.75 / L	white	Z+F	17,0	10,0	500	o. r.	o. r.	o. r.	
90125	2x 0.75 / N	grey	DIN	15,0	8,0	500	o. r.	o. r.	o. r.	
91661	2x 0.75 / N	light blue	DIN	15,0	8,0	500	o. r.	o. r.	o. r.	
91624	2x 0.75 / N	white	Z+F	15,0	8,0	500	o. r.	o. r.	o. r.	
91653	2x 1 / L	red	DIN	17,0	10,0	500	o. r.	o. r.	o. r.	
91654	2x 1 / L	yellow	Z+F	17,0	10,0	500	o. r.	o. r.	o. r.	
90126	2x 1 / N	red	DIN	15,0	8,0	500	o. r.	o. r.	o. r.	
91625	2x 1 / N	yellow	Z+F	15,0	8,0	500	o. r.	o. r.	o. r.	
91655	2x 1.5 / L	black	DIN	20,0	12,0	500	o. r.	o. r.	o. r.	
91672	2x 1.5 / L	red	Z+F	20,0	12,0	500	o. r.	o. r.	o. r.	
90127	2x 1.5 / N	black	DIN	16,0	8,0	500	o. r.	o. r.	o. r.	
91662	2x 1.5 / N	red	Z+F	16,0	8,0	500	o. r.	o. r.	o. r.	
91656	2x 2.5 / L	blue	DIN	21,5	13,0	250	o. r.	o. r.	o. r.	
91673	2x 2.5 / L	grey	Telemecanique	21,5	13,0	250	o. r.	o. r.	o. r.	
90128	2x 2.5 / N	blue	DIN	18,5	10,0	250	o. r.	o. r.	o. r.	
91663	2x 2.5 / N	grey	Telemecanique	18,5	10,0	250	o. r.	o. r.	o. r.	
91626	2x 4 / N	grey	DIN	23,0	12,0	100	o. r.	o. r.	o. r.	
91664	2x 4 / N	orange	Telemecanique	23,0	12,0	100	o. r.	o. r.	o. r.	
91627	2x 6 / N	yellow	DIN	26,0	14,0	100	o. r.	o. r.	o. r.	
91665	2x 6 / N	green	Telemecanique	26,0	14,0	100	o. r.	o. r.	o. r.	
91666	2x 6 / N	black	Z+F	26,0	14,0	100	o. r.	o. r.	o. r.	
91628	2x 10 / N	red	DIN	26,0	14,0	100	o. r.	o. r.	o. r.	
91667	2x 10 / N	brown	Telemecanique	26,0	14,0	100	o. r.	o. r.	o. r.	
91668	2x 10 / N	ivory	Z+F	26,0	14,0	100	o. r.	o. r.	o. r.	
91629	2x 16 / N	blue	DIN	30,0	14,0	50	o. r.	o. r.	o. r.	
91669	2x 16 / N	ivory	Telemecanique	30,0	14,0	50	o. r.	o. r.	o. r.	
91670	2x 16 / N	green	Z+F	30,0	14,0	50	o. r.	o. r.	o. r.	

Dimensions and specifications may be changed without prior notice.

o. r. = on request