

# E cable tie

stainless steel



## Cable binder

Cable tie made of stainless steel with ball lock for use in extreme conditions, such as high temperatures, aggressive environment, high tensile load.

## Material

Stainless steel 1.4401 / AISI 316

## Technical data

Temperature range: -80°C up to +538°C

## Properties

Corrosion and radiation resistant, anti-magnetic, resistant to high temperatures and aggressive chemicals

## Note

Approvals: GL, DNV, Lloyd's, UL

Part no.	Length mm	Width mm	Bundle Ø mm	Capacity N	Unit	Net EUR/100 items at a purchase of		
						up to 1000	1001 - 5000	5001 - 10000
90900	150,0	4,6	44,0	445,0	100	o. r.	o. r.	o. r.
90901	200,0	4,6	50,0	445,0	100	o. r.	o. r.	o. r.
90902	290,0	4,6	75,0	445,0	100	o. r.	o. r.	o. r.
90903	360,0	4,6	102,0	445,0	100	o. r.	o. r.	o. r.
90904	200,0	7,9	50,0	1112,0	100	o. r.	o. r.	o. r.
90905	290,0	7,9	75,0	1112,0	100	o. r.	o. r.	o. r.
90906	360,0	7,9	102,0	1112,0	100	o. r.	o. r.	o. r.
90907	520,0	7,9	152,0	1112,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request