

HELUcond PA6 UL corrugated tubes, polyamide

heavy duty



HELUcond PA6-UL-F/B

Heavy-duty cable protection tube for heavy-duty mechanical applications.

- high load rating

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Mod. Polyamide PA 6

Flammability acc. to UL 94: V0

- halogen-free
- cadmium-free

Properties

resistant to a multitude of

- fuels
- mineral oils
- greases
- weak bases
- weak acids

Note

UL recognized / UR

Suitable connection glands:

HELUquick, HSSV.

Technical data

Temperature range: -40°C up to +140°C

Temperature range temporary up to +160°C

Capacity/100mm NW 16/17: approx. 750 N

fine profile / PA6-UL-F

Part no. grey								
Part no. black	trade size mm	inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of			
					up to 100	101 - 500	501 - 1000	
920384	920394	7,5	6,4	10,0	50	o. r.	o. r.	o. r.
920385	920395	10,0	9,0	13,0	50	o. r.	o. r.	o. r.
920386	920396	12,0	11,0	15,8	50	o. r.	o. r.	o. r.
920387	920397	17,0	16,6	21,0	50	o. r.	o. r.	o. r.
920388	920398	23,0	21,6	28,5	50	o. r.	o. r.	o. r.

coarse profile / PA6-UL-B

Part no. grey	Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
						up to 100	101 - 500	501 - 1000
920389	920399	16,0	15,3	21,0	50	o. r.	o. r.	o. r.
920390	920400	21,0	21,6	28,5	50	o. r.	o. r.	o. r.
920391	920401	29,0	27,5	34,5	25	o. r.	o. r.	o. r.
920392	920402	36,0	35,0	42,5	25	o. r.	o. r.	o. r.
920393	920403	48,0	45,5	54,5	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request