

HELUcond PFA corrugated tubes, PFA

high temperature



new

HELUcond PFA

Excellent thermal, electrical and chemical properties; abrasion resistance and dimensionally stable.

Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Chemical plants
- Heating and air-conditioning technology

Material

PFA
UV-resistant

Flammability acc. to UL 94: V0

Properties

resistant to a multitude of

- fuels
- cleaning agents
- lubricants
- acids and alkalis

Note

Suitable connection glands:
HELUquick, HSSV

Technical data

Temperature range: -200°C up to +260°C

fine profile

Part no. black	trade size mm	Inner Ø mm	Outer Ø mm	Per metres	Net EUR/100 metres at a purchase of		
					up to 100	101 - 500	501 - 1000
905584	4,5	4,4	6,8	100	o. r.	o. r.	o. r.
905585	7,5	7,6	10,7	50	o. r.	o. r.	o. r.
905586	10,0	9,8	13,0	50	o. r.	o. r.	o. r.
905587	13,0	12,4	16,0	50	o. r.	o. r.	o. r.
905588	14,0	13,8	17,8	50	o. r.	o. r.	o. r.
905589	17,0	16,6	21,1	50	o. r.	o. r.	o. r.
905590	23,0	23,0	28,6	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request