

HELUTOP® sealing inserts



HELUTOP® HT protection tab

Protection tab HT for sealing of empty cable glands HELUTOP® HT

Material

Polyamide 6

Colours: black


Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Note

UV-resistant (RAL 9005).

*Protection tab 903492 only for cable glands type HT and HT-MS with clamping range 5-10mm.



Dimensions

D	Outer diameter head
d	Outer diameter insert
H	Height total
h	Height head

Part no.	Size metric	Outer diameter head mm	Outer diameter insert mm	Height total mm	Height head mm	Unit	Net EUR/100 items at a purchase of		
							5 - 100	105 - 500	505 - 1000
903492*	M16 x 1,5	13,5	10,0	20,5	5,5	100	o. r.	o. r.	o. r.
903493	M20 x 1,5	16,0	12,0	18,0	8,0	100	o. r.	o. r.	o. r.
903494	M25 x 1,5	20,0	16,5	18,5	7,5	100	o. r.	o. r.	o. r.
903495	M32 x 1,5	24,0	20,5	21,0	9,0	100	o. r.	o. r.	o. r.
903496	M40 x 1,5	32,0	27,5	25,0	9,0	100	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request