

Incision sealing ring



Incision sealing ring

Incision sealing rings for universal cable inlet through large cable clamping areas.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

chloroprene-rubber (CR)

Colours: black

Note


Incision sealing rings for PG thread:

Material: NR

Temperature range: -40°C up to +90°C

Technical data

Temperature range: -30°C up to +120°C



Dimensions

D Outer diameter

d Inner diameter

h Thickness

for metric thread

Part no.	Size	Inner Ø mm	Outer Ø mm	incisions mm	Thickness mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
94860	M12 x 1,5	5,0	10,7	-	5,0	100	o. r.	o. r.	o. r.
94861	M16 x 1,5	3,0	13,8	39938	5,5	100	o. r.	o. r.	o. r.
94863	M20 x 1,5	4,0	17,7	7/10/13	6,0	100	o. r.	o. r.	o. r.
94865	M25 x 1,5	8,5	22,5	11/14/17	8,0	100	o. r.	o. r.	o. r.
94866	M32 x 1,5	16,0	29,5	19/21/24	9,5	100	o. r.	o. r.	o. r.
94867	M40 x 1,5	23,0	37,5	26/29/32	11,0	50	o. r.	o. r.	o. r.
94868	M50 x 1,5	32,0	47,5	35/38/41	12,0	50	o. r.	o. r.	o. r.
94869	M63 x 1,5	41,0	60,3	44/47/50	14,0	50	o. r.	o. r.	o. r.

for PG thread

Part no.	Size	Inner Ø mm	Outer Ø mm	incisions mm	Thickness mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
96357	9	5,0	13,3	7,5/10	5,5	100	o. r.	o. r.	o. r.
96358	11	7,5	16,5	10/12,5	6,0	100	o. r.	o. r.	o. r.
96359	13,5	7,5	18,3	10/12,5	6,0	100	o. r.	o. r.	o. r.
96360	16	7,5	20,4	10/12,5/15	7,0	100	o. r.	o. r.	o. r.
96361	21	10,0	25,9	13/16/19	8,0	100	o. r.	o. r.	o. r.
96362	29	18,0	34,7	21/24/27	9,5	100	o. r.	o. r.	o. r.
96363	36	24,0	44,7	27/30/33	12,0	100	o. r.	o. r.	o. r.
96364	42	30,0	51,7	33/36/39	14,0	50	o. r.	o. r.	o. r.
96365	48	36,0	56,9	39/42/45	14,0	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request