

LT-E-UI conduit gland - straight

stainless steel



new

LT-E-UI straight

LIQUIDTIGHT gland for stainless steel protection tubes UI. The conical earthing sleeve offers maximum surface contact for optimum sealing and earthing.

Material

stainless steel
Grounding sleeve: Brass, nickel plated
Seal: Brass, nickel plated
Moulded seal: NBR

Technical data

Protection class: IP 40
Temperature range: -55°C up to +260°C

Application

- Robot construction
- Steel and aluminium foundry industry
- Machine and apparatus building
- Off-shore industry
- Security
- Metal, glass and ceramics industry

metric thread

Part no.	Size	Tube outer Ø mm	Thread length mm	Min. inner Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905812	M16 x 1,5	12,5	12,0	6,8	50	o. r.	o. r.	o. r.
905813	M16 x 1,5	16,0	12,0	9,8	50	o. r.	o. r.	o. r.
905814	M20 x 1,5	12,5	13,0	6,8	50	o. r.	o. r.	o. r.
905815	M20 x 1,5	16,0	13,0	9,8	50	o. r.	o. r.	o. r.
905816	M20 x 1,5	21,0	13,0	13,9	50	o. r.	o. r.	o. r.
905817	M25 x 1,5	26,0	15,0	18,5	25	o. r.	o. r.	o. r.
905818	M32 x 1,5	30,0	15,0	22,8	10	o. r.	o. r.	o. r.
905819	M40 x 1,5	39,0	16,0	30,8	5	o. r.	o. r.	o. r.

PG thread

Part no.	Size	Tube outer Ø mm	Thread length mm	Min. inner Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905820	11	12,5	12,0	6,8	50	o. r.	o. r.	o. r.
905821	11	16,0	12,0	9,8	50	o. r.	o. r.	o. r.
905822	16	21,0	13,0	13,9	50	o. r.	o. r.	o. r.
905823	21	26,0	15,0	18,5	25	o. r.	o. r.	o. r.
905824	29	30,0	15,0	22,8	10	o. r.	o. r.	o. r.
905825	36	39,0	16,0	30,8	5	o. r.	o. r.	o. r.

NPT thread

Part no.	Size	Tube outer Ø mm	Thread length mm	Min. inner Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905826	1/2"	12,5	12,0	6,8	50	o. r.	o. r.	o. r.
905827	1/2"	16,0	12,0	9,8	50	o. r.	o. r.	o. r.
905828	1/2"	21,0	13,0	13,9	50	o. r.	o. r.	o. r.
905829	3/4"	26,0	15,0	18,5	25	o. r.	o. r.	o. r.
905830	1"	30,0	15,0	22,8	10	o. r.	o. r.	o. r.
905831	1 1/4"	39,0	16,0	30,8	5	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request