


BUS Cables

Profibus PA



Long Distance



Type

Cable structure

Inner conductor diameter:
Core insulation:
Core colours:
Stranding element:
Shielding 1:
Shielding 2:
Total shielding:
Outer sheath material:
Cable external diameter:
Outer sheath colour:

Hazardous areas

1x2x1.6/3.2 mm

Copper, bare (AWG 16/7)
PE
rd, gn
2 cores + 2 fillers stranded together
Polyester foil over stranded bundle
Polyester foil, aluminium-lined
Cu braid, tinned
PVC
approx. 9,5 mm ± 0,5 mm
Blue

Non-hazardous areas

1x2x1.6/3.2 mm

Copper, bare (AWG 16/7)
PE
rd, gn
2 cores + 2 fillers stranded together
Polyester foil over stranded bundle
Polyester foil, aluminium-lined
Cu braid, tinned
PVC
approx. 9,5 mm ± 0,5 mm
Black

Electrical data

Characteristic impedance:
Conductor resistance, max.:
Insulation resistance, min.:
Loop resistance:
Mutual capacitance:
Nominal voltage:
Test voltage:
Attenuation:

100 Ohm ± 20 %
24 Ohm/km
1 GOhm x km
48 Ohm/km max.
60 nF/km nom.
300 V
1 kV
39 kHz ≤ 2,7 dB/km

100 Ohm ± 20 %
24 Ohm/km
1 GOhm x km
48 Ohm/km max.
60 nF/km nom.
300 V
1 kV
39 kHz ≤ 2,7 dB/km

Technical data

Weight:
bending radius, repeated:
Operating temperature range min.:
Operating temperature range max.:
Caloric load, approx. value:
Copper weight:

approx. 110 kg/km
150 mm
-40°C
+70°C
1,57 MJ/m
62,00 kg/km

approx. 110 kg/km
150 mm
-40°C
+70°C
1,57 MJ/m
62,00 kg/km

Norms

Applicable standards:
UL Style:

Profibus acc. to DIN 19245 T3 and EN50170
UL Style 2571

Profibus acc. to DIN 19245 T3 and EN50170
UL Style 2571

Application

This Profibus PA line is used in the area of process automation, among other things in the chemical industry. This cable is an economical solution for the cell and field area. For the information exchange between different automation systems as well as for communication with the connected decentralized field units, serial field bus systems are used. The types mentioned here are suitable for ex and not-ex installation and are equipped with a special PVC-sheath.

Part no.

800650, Profibus PA

800715, Profibus PA

Dimensions and specifications may be changed without prior notice.