

RE PA-ATEX reducer

explosive area



Reducer RE-PA-ATEX

For use in explosive areas.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Installation technology
- Control cabinet construction

Material

Polyamide

Colours: black
RAL: 9005

- halogen-free
- phosphor-free
- silicone-free
- cadmium-free


Note

Approval: PTB 04 ATEX 1040X

Technical data

Protection class: IP 66

Temperature range: -20°C up to +70°C



from metric to metric

Part no.	Size metr. outside	Size metr. inside	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
904428	M25 x 1,5	M12 x 1,5	100	o. r.	o. r.	o. r.
904429	M25 x 1,5	M16 x 1,5	100	o. r.	o. r.	o. r.
904430	M25 x 1,5	M20 x 1,5	100	o. r.	o. r.	o. r.
904431	M32 x 1,5	M16 x 1,5	50	o. r.	o. r.	o. r.
904432	M32 x 1,5	M20 x 1,5	50	o. r.	o. r.	o. r.
904433	M32 x 1,5	M25 x 1,5	50	o. r.	o. r.	o. r.
904434	M40 x 1,5	M20 x 1,5	25	o. r.	o. r.	o. r.
904435	M40 x 1,5	M25 x 1,5	25	o. r.	o. r.	o. r.
904436	M40 x 1,5	M32 x 1,5	25	o. r.	o. r.	o. r.
904437	M50 x 1,5	M20 x 1,5	5	o. r.	o. r.	o. r.
904438	M50 x 1,5	M25 x 1,5	5	o. r.	o. r.	o. r.
904439	M50 x 1,5	M32 x 1,5	5	o. r.	o. r.	o. r.
904440	M50 x 1,5	M40 x 1,5	5	o. r.	o. r.	o. r.
904441	M63 x 1,5	M20 x 1,5	5	o. r.	o. r.	o. r.
904442	M63 x 1,5	M25 x 1,5	5	o. r.	o. r.	o. r.
904443	M63 x 1,5	M32 x 1,5	5	o. r.	o. r.	o. r.
904444	M63 x 1,5	M40 x 1,5	5	o. r.	o. r.	o. r.
904445	M63 x 1,5	M50 x 1,5	5	o. r.	o. r.	o. r.

from metric to metric - high-profile design

Part no.	Size metr. outside	Size metr. inside	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
904446	M16 x 1,5	M12 x 1,5	100	o. r.	o. r.	o. r.
904448	M20 x 1,5	M16 x 1,5	100	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request