

RE round reducer



RE

The reducer made of brass. Transition from large to small thread.

Material


Brass, nickel plated

Technical data

Temperature range: up to +200°C

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Installation technology
- Control cabinet construction



Dimensions

G Thread size outside
IG Thread size inside
GL Thread length
D Outer diameter

from metric to metric

Part no.	Size metr. outside	Size metr. inside	Thread length mm	Outer Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
94065	M16 x 1,5	M12 x 1,5	5,0	18,0	100	o. r.	o. r.	o. r.
94067	M20 x 1,5	M12 x 1,5	6,0	22,0	100	o. r.	o. r.	o. r.
94068	M20 x 1,5	M16 x 1,5	6,0	22,0	100	o. r.	o. r.	o. r.
94070	M25 x 1,5	M16 x 1,5	7,0	27,0	50	o. r.	o. r.	o. r.
904407	M25 x 1,5	M20 x 1,5	7,0	27,0	100	o. r.	o. r.	o. r.
904408	M32 x 1,5	M20 x 1,5	8,0	34,0	25	o. r.	o. r.	o. r.
94074	M32 x 1,5	M25 x 1,5	8,0	34,0	50	o. r.	o. r.	o. r.
904409	M40 x 1,5	M25 x 1,5	8,0	43,0	25	o. r.	o. r.	o. r.
94077	M40 x 1,5	M32 x 1,5	8,0	43,0	25	o. r.	o. r.	o. r.
94079	M50 x 1,5	M32 x 1,5	9,0	53,0	10	o. r.	o. r.	o. r.
94080	M50 x 1,5	M40 x 1,5	9,0	53,0	25	o. r.	o. r.	o. r.
94082	M63 x 1,5	M40 x 1,5	10,0	66,0	10	o. r.	o. r.	o. r.
94083	M63 x 1,5	M50 x 1,5	10,0	66,0	10	o. r.	o. r.	o. r.

from PG to PG

Part no.	Size PG outside	Size PG inside	Thread length mm	Outer Ø mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
904410	9	7	6,0	17,0	100	o. r.	o. r.	o. r.
904411	11	7	6,0	20,0	100	o. r.	o. r.	o. r.
904412	11	9	6,0	20,0	100	o. r.	o. r.	o. r.
904413	13,5	9	6,5	22,0	100	o. r.	o. r.	o. r.
904414	16	7	6,5	24,0	50	o. r.	o. r.	o. r.
904415	16	13,5	6,5	24,0	100	o. r.	o. r.	o. r.
904416	21	13,5	7,0	30,0	50	o. r.	o. r.	o. r.
904417	21	16	7,0	30,0	50	o. r.	o. r.	o. r.
904418	29	16	8,0	39,0	25	o. r.	o. r.	o. r.
904419	29	21	8,0	39,0	25	o. r.	o. r.	o. r.
904420	42	29	10,0	57,0	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request