

# UNI-DICHT ZUG sealing inserts

for increased strain relief



new

## UNI-DICHT ZUG

Colour coded sealing inserts made by TPE for increased strain relief. For populating UNI-DICHT body glands made of plastic or brass.

### Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

## Material

TPE

- halogen-free
- phosphor-free
- silicone-free
- cadmium-free

## Note

Assignment to gland body: see table

## Technical data

Temperature range: -20°C up to +100°C

Part no.	Size PG	Size metric	Sealing insert colour	Cable Ø from / to mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
905690	-	M12 x 1,5	yellow	4,0 - 6,5	50	o. r.	o. r.	o. r.
905691	7	-	yellow	4,0 - 6,5	50	o. r.	o. r.	o. r.
905692	9	M16 x 1,5	yellow	4,0 - 6,5	50	o. r.	o. r.	o. r.
905693	9	M16 x 1,5	black	5,5 - 9,0	50	o. r.	o. r.	o. r.
905694	11	-	black	5,5 - 9,0	50	o. r.	o. r.	o. r.
905695	11	-	green	6,0 - 10,0	50	o. r.	o. r.	o. r.
905696	-	M20 x 1,5	black	5,5 - 9,0	50	o. r.	o. r.	o. r.
905697	-	M20 x 1,5	green	6,0 - 10,0	50	o. r.	o. r.	o. r.
905698	-	M20 x 1,5	red	8,0 - 12,0	50	o. r.	o. r.	o. r.
905699	13,5	M20 x 1,5	black	5,5 - 9,0	50	o. r.	o. r.	o. r.
905700	13,5	M20 x 1,5	green	6,0 - 10,0	50	o. r.	o. r.	o. r.
905701	13,5	M20 x 1,5	red	8,0 - 12,0	50	o. r.	o. r.	o. r.
905702	16	M25 x 1,5	green	6,0 - 10,0	50	o. r.	o. r.	o. r.
905703	16	M25 x 1,5	red	8,0 - 12,0	50	o. r.	o. r.	o. r.
905704	16	M25 x 1,5	white	12,0 - 15,0	50	o. r.	o. r.	o. r.
905705	21	M32 x 1,5	red	8,0 - 12,0	25	o. r.	o. r.	o. r.
905706	21	M32 x 1,5	white	12,0 - 15,0	25	o. r.	o. r.	o. r.
905707	21	M32 x 1,5	blue	14,0 - 17,0	25	o. r.	o. r.	o. r.
905708	21	M32 x 1,5	brown	16,0 - 20,0	25	o. r.	o. r.	o. r.
905709	29	M40 x 1,5	brown	16,0 - 20,0	10	o. r.	o. r.	o. r.
905710	29	M40 x 1,5	orange	20,0 - 24,0	10	o. r.	o. r.	o. r.
905711	29	M40 x 1,5	light yellow	23,0 - 27,0	10	o. r.	o. r.	o. r.
905712	36	M50 x 1,5	anthracite	27,0 - 31,5	5	o. r.	o. r.	o. r.
905713	36	M50 x 1,5	pink	32,0 - 36,0	5	o. r.	o. r.	o. r.
905714	42	-	white	34,0 - 40,0	5	o. r.	o. r.	o. r.
905715	48	M63 x 1,5	white	39,0 - 43,0	5	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request