

VS-O screw plug with O-ring



VS-O

The screwed plug made of brass with an O-ring.

Material

Brass, nickel plated
O-ring: NBR


Technical data

Protection class: IP 68

Temperature range: -40°C up to +80°C

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction



Dimensions

G Thread size
GL Thread length

metric thread

Part no.	Size Metr.	Thread length mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
92600	M12 x 1,5	5,0	100	o. r.	o. r.	o. r.
92601	M16 x 1,5	5,0	100	o. r.	o. r.	o. r.
92602	M20 x 1,5	6,0	100	o. r.	o. r.	o. r.
92603	M25 x 1,5	7,0	100	o. r.	o. r.	o. r.
92604	M32 x 1,5	8,0	50	o. r.	o. r.	o. r.
92605	M40 x 1,5	8,0	50	o. r.	o. r.	o. r.
92606	M50 x 1,5	9,0	25	o. r.	o. r.	o. r.
92607	M63 x 1,5	10,0	10	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG	Thread length mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
96763	7	5,0	100	o. r.	o. r.	o. r.
96169	9	5,0	100	o. r.	o. r.	o. r.
96889	11	5,0	100	o. r.	o. r.	o. r.
96654	13,5	6,0	100	o. r.	o. r.	o. r.
96170	16	6,0	100	o. r.	o. r.	o. r.
96171	21	6,0	100	o. r.	o. r.	o. r.
96650	29	8,0	50	o. r.	o. r.	o. r.
96649	36	9,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request