

VSK-EX screw plug

explosive area



VSK-EX

The screwed plug for explosive area to DIN EN 50014 and DIN EN 50019.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Polyamide
O-ring: NBR

Colours: black
RAL: 9005

- halogen-free
- phosphor-free


Note

Approval: DMT 03 ATEX E 049

Technical data

Protection class: IP 68 - 10 bar / IP 69K

Temperature range: -20°C up to +90°C



Dimensions

G Thread size
GL Thread length
H Height
SW Spanner size
E Angle size

metric thread

Part no. black RAL 9005	Size Metr.	Thread length mm	Height mm	Spanner size mm	Angle size mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
98114	M12 x 1,5	8,5	13,0	15	16,5	100	o. r.	o. r.	o. r.
98115	M16 x 1,5	8,5	13,0	19	20,5	100	o. r.	o. r.	o. r.
96793	M20 x 1,5	9,0	14,5	24	25,5	100	o. r.	o. r.	o. r.
98116	M25 x 1,5	10,5	16,0	28	30,5	100	o. r.	o. r.	o. r.
97763	M32 x 1,5	11,5	17,5	36	38,0	50	o. r.	o. r.	o. r.
98117	M40 x 1,5	11,5	18,0	46	48,0	25	o. r.	o. r.	o. r.
98118	M50 x 1,5	13,5	20,0	55	60,0	20	o. r.	o. r.	o. r.
98119	M63 x 1,5	14,5	21,0	70	75,0	20	o. r.	o. r.	o. r.

PG thread

Part no. black RAL 9005	Size PG	Thread length mm	Height mm	Spanner size mm	Angle size mm	Unit	Net EUR/100 items at a purchase of		
							up to 100	101 - 500	501 - 1000
91447	7	8,5	13,0	15	16,5	100	o. r.	o. r.	o. r.
91448	9	8,5	13,0	19	20,5	100	o. r.	o. r.	o. r.
91449	11	9,0	14,5	24	25,5	100	o. r.	o. r.	o. r.
91450	13,5	9,0	14,5	24	25,5	100	o. r.	o. r.	o. r.
91451	16	10,5	16,0	28	30,5	100	o. r.	o. r.	o. r.
91452	21	11,5	17,5	36	38,0	100	o. r.	o. r.	o. r.
91453	29	11,5	18,0	46	48,0	50	o. r.	o. r.	o. r.
91454	36	13,5	20,0	55	60,0	25	o. r.	o. r.	o. r.
91455	42	13,5	20,0	60	65,0	20	o. r.	o. r.	o. r.
91456	48	14,5	21,0	70	75,0	20	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request