

VS screw plug



VS

The screwed plug made of brass.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material

Brass, nickel plated


Note

Screw plugs for metric threads larger than M63x1,5 on request.

Technical data

Protection class: IP 54

Temperature range: up to +200°C



Dimensions

G Thread size
GL Thread length

metric thread

Part no.	Size Metr.	Thread length mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
98128	M12 x 1,5	5,0	100	o. r.	o. r.	o. r.
98129	M16 x 1,5	5,0	100	o. r.	o. r.	o. r.
98130	M20 x 1,5	6,5	100	o. r.	o. r.	o. r.
98131	M25 x 1,5	7,0	100	o. r.	o. r.	o. r.
98132	M32 x 1,5	8,0	50	o. r.	o. r.	o. r.
98133	M40 x 1,5	8,5	50	o. r.	o. r.	o. r.
98134	M50 x 1,5	9,0	25	o. r.	o. r.	o. r.
98135	M63 x 1,5	10,0	10	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG	Thread length mm	Unit	Net EUR/100 items at a purchase of		
				up to 100	101 - 500	501 - 1000
90620	7	5,0	100	o. r.	o. r.	o. r.
90621	9	6,0	100	o. r.	o. r.	o. r.
90622	11	6,0	100	o. r.	o. r.	o. r.
90623	13,5	6,5	100	o. r.	o. r.	o. r.
90624	16	6,5	100	o. r.	o. r.	o. r.
90625	21	7,0	50	o. r.	o. r.	o. r.
90626	29	8,0	25	o. r.	o. r.	o. r.
90627	36	9,0	50	o. r.	o. r.	o. r.
90628	42	10,0	25	o. r.	o. r.	o. r.
90629	48	10,0	25	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request