

WN blanking plug

closed



WN closed

Self-sealing grommet with flexible plastic lead-through diaphragm for simple cable inlet.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet technology

Material

Polyethylene

- halogen-free


Note

Open blanking plugs: on request.

Technical data

Protection class: IP 54

Temperature range: -20°C up to +70°C



Dimensions

G Thread size
GL Thread length

metric thread

Part no.	Size Metr.	Cable Ø from / to mm	Thread length mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
94120	M12 x 1,5	3,0 - 5,0	10,0	100	o. r.	o. r.	o. r.
94121	M16 x 1,5	5,0 - 10,0	10,0	100	o. r.	o. r.	o. r.
94122	M20 x 1,5	8,0 - 13,5	12,0	100	o. r.	o. r.	o. r.
94123	M25 x 1,5	9,0 - 16,0	12,0	100	o. r.	o. r.	o. r.
94124	M32 x 1,5	11,0 - 22,0	14,0	50	o. r.	o. r.	o. r.
94125	M40 x 1,5	17,0 - 24,0	16,0	25	o. r.	o. r.	o. r.
94126	M50 x 1,5	22,0 - 35,0	18,0	10	o. r.	o. r.	o. r.
94127	M63 x 1,5	24,0 - 43,0	20,0	10	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG	Cable Ø from / to mm	Thread length mm	Unit	Net EUR/100 items at a purchase of		
					up to 100	101 - 500	501 - 1000
90116	9	6,0 - 8,0	12,0	100	o. r.	o. r.	o. r.
90117	11	7,0 - 10,0	14,0	100	o. r.	o. r.	o. r.
90118	13,5	9,0 - 12,0	17,0	100	o. r.	o. r.	o. r.
90119	16	9,0 - 14,0	19,0	100	o. r.	o. r.	o. r.
90120	21	11,0 - 17,0	24,0	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request