


WV

Profile for simple cable insertion.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material


Die-cast zinc
O-ring: chloroprene-rubber (CR)

Technical data

Protection class: IP 65

Temperature range: -20°C up to +100°C

Test standard: EN50262


Dimensions

G Thread size outside
GL Thread length
IG Thread size inside
H Height without thread

from metric to metric

Part no.	Size Metr. outside	Thread length mm	Size Metr. inside	Height mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
98561	M16 x 1,5	7,0	M16 x 1,5	25,0	25	o. r.	o. r.	o. r.
98562	M20 x 1,5	7,0	M20 x 1,5	30,0	25	o. r.	o. r.	o. r.
98563	M25 x 1,5	7,0	M25 x 1,5	35,0	25	o. r.	o. r.	o. r.
98564	M32 x 1,5	10,0	M32 x 1,5	45,0	10	o. r.	o. r.	o. r.

from PG to PG

Part no.	Size PG outside	Thread length mm	Size PG inside	Height mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
99020	9	7,0	9	23,0	25	o. r.	o. r.	o. r.
99021	11	7,0	11	28,0	25	o. r.	o. r.	o. r.
99022	13,5	7,0	13,5	32,0	25	o. r.	o. r.	o. r.
99023	16	7,0	16	27,0	25	o. r.	o. r.	o. r.
99024	21	10,0	21	38,0	10	o. r.	o. r.	o. r.
99025	29	11,0	29	46,0	10	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request