

ZES cable gland

with strain relief and incision sealing ring



ZES

The hexagonal brass strain relief gland with incision sealing ring.

Application

- Plant and machine construction
- Robot construction
- Automation technology
- Vehicle construction and shipbuilding
- Rail technology
- Installation technology
- Control cabinet construction

Material


Brass, nickel plated
Moulded seal: NBR
Thrust rings: Galvanised steel

Technical data

Protection class: IP 54

Temperature range: -20°C up to +60°C

Test standard: EN50262



Dimensions

G Thread size
GL Thread length
SW Spanner size

metric thread

Part no.	Size Metr.	Cable Ø incisions from / to mm	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
90275	M12 x 1,5	5/7	5,0	14	50	o. r.	o. r.	o. r.
90276	M16 x 1,5	5,5/9	5,0	18	50	o. r.	o. r.	o. r.
90278	M20 x 1,5	7/10/13	6,0	22	50	o. r.	o. r.	o. r.
90279	M20 x 1,5	9/11/13	6,0	24	50	o. r.	o. r.	o. r.
90280	M25 x 1,5	11/14/17	7,0	30	25	o. r.	o. r.	o. r.
90281	M32 x 1,5	19/21/24	8,0	39	20	o. r.	o. r.	o. r.
90282	M40 x 1,5	26/29/32	8,0	50	10	o. r.	o. r.	o. r.
90283	M50 x 1,5	35/38/41	9,0	57	5	o. r.	o. r.	o. r.
90284	M63 x 1,5	44/47/50	10,0	66	5	o. r.	o. r.	o. r.

PG thread

Part no.	Size PG	Cable Ø incisions from / to mm	Thread length mm	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
90569	7	7	5,0	14	50	o. r.	o. r.	o. r.
90570	9	5/7,5/10	6,0	17	50	o. r.	o. r.	o. r.
90571	11	7,5/10/12,5	6,0	20	50	o. r.	o. r.	o. r.
90572	13,5	7,5/10/12,5	6,5	22	50	o. r.	o. r.	o. r.
90573	16	7,5/10/12,5/15	6,5	24	50	o. r.	o. r.	o. r.
90574	21	10/13/16/19	7,0	30	25	o. r.	o. r.	o. r.
90575	29	18/21/24/27	8,0	40	25	o. r.	o. r.	o. r.
90576	36	24/27/30/33	9,0	50	10	o. r.	o. r.	o. r.
90577	42	30/33/36/39	10,0	57	5	o. r.	o. r.	o. r.
90578	48	36/39/42/45	10,0	64	5	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request